



LuK Service Info

Clutch slave cylinder 512 0050 10

Different versions

Vehicle

manufacturer: Citroën
Peugeot

Models:

Citroën: C-Elysee
C3 II
C4 Cactus
DS3
DS3 Cabriolet
Peugeot: 207 SW
207/207
208
301
2008 I



Image 1: Clutch slave cylinder 512 0050 10 (Version 1/original equipment)

See parts catalogue for current applications

Two different clutch slave cylinders can be supplied under part number 512 0050 10. One version corresponds to the original equipment in terms of appearance and handling, the other differs in both cases.

In version 1 (Fig. 1), the vehicle-side hydraulic line can be connected directly to the clutch slave cylinder using its line adapter. To bleed, release the lower retainer clip on the slave cylinder connection to the first detent position and pull the connector slightly out of the housing. After bleeding, return it to its initial position and lock the retainer clip.



Image 2: Clutch slave cylinder 512 0050 10 (version 2)

Before mounting version 2 (Fig. 2), the vehicle-side line adapter on the hydraulic line must be removed. Only then can a connection be made to this clutch slave cylinder. To bleed, open the breather valve by manually turning it 180° to the right. After bleeding, close the valve by turning it in the opposite direction.

Despite their different designs, both clutch slave cylinders can be used without restrictions for the vehicles specified in the catalogue.

Please observe the vehicle manufacturer specifications!

You want more? We can help!

Phone: +44 (0) 1432 264 264
Fax: +44 (0) 1432 375 760
aftermarket.uk@schaeffler.com
www.repxpert.co.uk